It is our commitment to provide the service with the highest standard of safety, quality and reliability that meet the specified requirements and expectations.

Wireless Traffic Light Using Solar Energy

KAF ITAC WIRELESS SOLAR TRAFFIC LIGHT SYSTEM



KAF iTAC Wireless Solar Traffic Light System is built with state-of-art modern wireless technologies to eliminate obstacles faced in existing conventional wired traffic light control sytems.

Wireless Solar Traffic Light Controller is completely wireless communicating over radio data being transmitted between master controller and signal group controller.

It is completely solar-powered and environment friendly solution incorporated with all world modern traffic light systems.provide solution that utilizes solar energy to power traffic lights and associated signaling equipment. This system is designed to enhance road safety and reduce energy consumption.


Key Benefits:

- Less waiting time hence lower carbon emissions
- Enhanced travel experience with improved efficiency
- Flexsible and modular system design
- Adaptive Traffic Light Control
- Real Time Monitoring
- · Lowering maintenance cost
- Improved Junction Throughput
- Remote Configuration
- Cycle time optimization

Wireless Traffic Light
System | Solar
Powered | Energy and
Cost Saving

Your Easy Solution'


System Operational Drawing for Wireless Traffic Light Controller



- System Wireless Comunication
- Master Controller Functional
- Solar Energy Consumption
- Cost-effective

It is our commitment to provide the service with the highest standard of safety, quality and reliability that meet the specified requirements and expectations.

COMPONENTS OF WIRELESS SOLAR TRAFFIC LIGHT **SYSTEM**





KAF iTAC Wireless Solar Traffic Light Controller

- 1. (Traffic lights) 12V and 24V DC LED traffic lights (vehicle and pedestrian lights).
- 2. (Solar Panel) High efficiency PV solar panel to collect sunshine energy.
- 3. (Light Pole) Rugged steel light pole specially designed for traffic.
- 4.(Cabinet) Steel container for Battery, traffic light controllers and charge
- 5. (Wireless Solar Traffic Light Controllers) 1 pole CPU/Host controller and others Lamp output/Receiver controllers.
- 6. (Battery) Power up traffic lights and traffic light controllers with storage energy in the daytime
- 7.(Charge Controller) Transfer solar energy to traffic lights, traffic light controllers and battery

Your Easy Solution"

KAF ITAC WIRELESS TRAFFIC LIGHT

SPECIFICATION

Backup Supply

Provides 5-8 days back up supply in rainy/cloudy days, and average 7-8 hour sun light in sunny days.

System expansion

Controller caters flexible system expansion, with 4 vehicle signal groups per pole (expandable upto 12 poles and 48 vehicle signal groups), 2 WVD channel per pole (expandable upto 12 poles and 24 WVD channel), 2 pedestrian inputs per pole.

Countdown Compatiblity

Compatible to 4 individual or 4 redundant wireless countdown.

Wireless Communication Compatiblity

Compatible with Wireless Communication Interface

(WVD).

Safety and Smart Features Configuration

Provide Dynamic Go-Green link traffic controllers, Conflict monitoring, double lights and opposite

Configuration

iTAC Windows and iTAC Mobile (Android/loS), Software, compatible with XAITS and Star intelligent transportation systems, compatible with REACT

Mechanical Features

Traffic signal controller complete with, Earthing system, 15 KA surge protection device, can be easily connected and interfaced to UTC existing devices.

iTAC Wireless CPU Controller (Master Slave) Specification

Microprocessor

32 bit intelligent microprocessor based.

Wireless CPU Features

wireless traffic light controller with embedded 3 vehicle signal groups, 2 WVD channel, 2 pedestrian inputs.

Vehicle Actuated

Support VA Multiplan i.e. VA Min, VA Max, VA Gap optimized for (48x10x7) discrete time windows, compatible with fixed time and dynamic timing Wireless Countdown System i.e Dash Countdown, Full display countdown, Jump countdown, Pedestrian system with Exclusive VA Allocation, Integrated Pedestrian Control.

Amber flashing

Log memory

Supports up to 3-4 years (fault logs & data).

Communication

Bluetooth, USB Port, RS232, RF Wireless Communication.

Power Consumption

150 Watt, Half Cut mono perc, mono crystalline solar panel. Deep Cycle 150AH tall tubular, sealed Lead acid battery.


Capacity Charger Rate

30A solar charge controller.

iTAC Wireless Lamp Output Controllers (Slave) Specification

Microprocessor	8 bit intelligent microprocessor based.
Wireless CPU Features	wireless traffic light controller with embedded configurable 1-4 vehicle signal groups, 2 WVD channel, 2 pedestrian inputs, intelligent CPU heartbeat detection.
Communication	RF Wireless Communication.
Amber flashing,	Compatible with independent flash yellow.
Power Consumption	150 Watt, Half Cut mono perc, mono crystalline solar panel.
Capacity	Deep Cycle 150AH tall tubular, sealed Lead acid battery.
Charger Rate	30A solar charge controller.

Master Slave Architecture of Junction Pole



Disclaimer

ADDRESS

NO.102, JALAN BUKIT UBI 25200 KUANTAN, PAHANG DARUL MAKMUR



CONTACT

TEL NO.: 09-5315333

MOBILE NO.: 019-2589137



EMAIL: info@kaf2u.com



WEBSITE: www.kaf2u.com